



MOUNT PIPE BRACKETS IN LINE WITH DOCK LEGS ON JOB SITE FOR BEST FIT. NOTE: DOCK LEGS MAY NOT BE IN LINE WHERE DOCK MAKES TURNS. MOUNT THIRD PIPE BRACKET TO DOCK FOR THE DEDICATED BENCH LEG

NOTES: TYPICAL INSTALLATION USES ONE DOCK LEG AND ONE EXTRA LEG DEDICATED TO THE BENCH

This drawing is the property of Great Northern Docks. All information contained within is proprietary. This drawing or copies of all or any part of this drawing may not be removed from Great Northern Docks premises without the approval of the company President.

ALL TOLERANCES +/- 1/16 INCH EXCEPT WHERE OTHERWISE NOTED. ALL ANGLES +/- 0.5 DEGREES EXCEPT OTHERWISE NOTED.

## GREAT NORTHERN DOCKS

### 5' WOOD BENCH

ITEM	QTY.	P/N	DESCRIPTION
1	6		2"x6" PRESSURE TREATED X 5'
2	8		5/16" X 3 1/2" GALV. CARR BOLT
3	8		5/16" GALV. HEX NUT
4	8		5/16" GALV. FLAT WASHER
5	24		#10 DECK SCREW X 3"
6	3	4071	4.5" PIPE BRACKET
7	1	9280	SIX PACK 3/8X2 1/2" CARR BOLTS, NUTS, WASHERS

SCALE: NTS      DRAWN BY: SJM      DATE: 12/01/09      5' BENCH      REV 0